

# 5200 MOUNT SERIES (5200/5200HT)

Versatile all-attitude isolators for vibration and shock protection.

## APPLICATIONS

- Airborne electronics and racking
- Ground transportation applications
- Severe random vibration environments
- Electric motors

## FEATURES


- All-attitude mounting with rugged, fail-safe construction
- Axial to radial stiffness of 1:0.6
- Low profile mounts
- Wide range of load ratings for both stationary and mobile environments

## BENEFITS

- Isolator provides effective vibration isolation in any attitude
- Fail-safe design captivates the mounted equipment even if the elastomeric elements should be destroyed

## LOAD RANGE

- 4 load ratings to 50 lbs. per mount



Barry 5200 Series Mounts are for applications where protection is required from shock, vibration or noise. The fail-safe, low profile construction of 5200 Series Isolators are ideal for use where space is at a minimum.

## Specifications

• Natural Frequency	15-40 Hertz
• Transmissibility at resonance	4.0 Max. (Hi-Damp Silicone) 10.0 Max. (Neoprene & Natural Rubber)
• Resilient Element	Hi-Damp Silicone, Neoprene, or Natural Rubber
• Standard Materials	Zinc plated steel
• Weight	5200 = 2.5 oz. 5200H = 3.5 oz.

## Environmental Data

- Hi-Damp Silicone version meets shock & vibration requirements of MIL-E-5400 with an operating temperature range of -67°F to +300°F (-55°C to +150°C).
- Neoprene version is available for use where temperature extremes are not encountered, but resistance to oil or ozone is required. Operational temperature range is -20°F to +180°F (-30°C to +83°C).